

## ECONOMY ILLUMINATOR

Although this illuminator has a **budget price** it is made with the same care found in higher priced models. It is constructed of *heavy gauge steel* and comes with an on/off switch, plexiglass viewing panel, four *stainless steel spring action film clips* and a film retainer ledge. The 14"x17" viewing area is illuminated by two F15T8/D daylight fluorescent bulbs.

DEPTH OF VIEWERS: 5.375"		EXTERIOR DIM		APPROX.	CATALOG
VIEWING AREA	WIDTH	HGT	SHIP WT		NO.
SingleBank	14"x17"	15.625"	18.25"	16lbs	200

ALL MEASUREMENTS ARE  $\pm \frac{1}{16}"$



**Finish:** Light Grey baked enamel

**Electrical:** Viewers operate on 120 volt, 60 Hz, .75 Amps AC per viewing area. Supplied with a 6' three conductor line cord. For special voltages consult factory.

## 12" X 24" ILLUMINATORS

Designed to view three 8"x10" or two 10"x12" films at one time, this superior illuminator with built in reflectors and two F20T12/D daylight fluorescent bulbs produces bright even illumination. **Surface** and **Recessed** models are all steel construction with your choice of *Gravity Film Grips* or *Spring Film Clip Holders*.

### **SURFACE MOUNTED MODELS**

DEPTH OF VIEWERS: 5.25"		EXTERIOR DIM		APPROX.	CATALOG NO.
VIEWING AREA	WIDTH	HGT	SHIP WT	GRAVITY GRIP	FILM CLIP
SingleBank	12"x24"	24.625"	13.5"	25 lbs	254T 254

### **RECESSED MODELS**

DEPTH OF VIEWERS: 5.25"		EXTERIOR DIM		WALL OPENING		APPROX.	CATALOG NO.
VIEWING AREA	WIDTH	HGT	WIDTH	HGT	SHIP WT	GRAVITY GRIP	FILM CLIP
Single Bank	12"x24"	24.625"	13.5"	24.875"	13.75"	26 lbs	254RT 254R

ALL MEASUREMENTS ARE  $\pm \frac{1}{16}"$



**Finish:** Light Grey baked enamel

**Electrical:** Viewers operate on 120 volt, 60 Hz, .75 Amps AC per viewing area. Supplied with a 6' three conductor line cord. For special voltages consult factory.

**NEED HELP IN SELECTING THE RIGHT ILLUMINATOR FOR YOUR APPLICATION? CALL US AT 800 - 347 - XRAY AND WE'LL BE HAPPY TO ASSIST YOU!**