

SAFELIGHTS

HIGH VISION SAFELIGHT

PRODUCES MORE USABLE LIGHT IN THE SAFE RANGE THAN CONVENTIONAL SAFELIGHTS

- FLUORESCENT BRIGHTER LIGHTING
- ECONOMICAL REUSABLE FILTER



	WIDTH	HGT	DEPTH
15 Watt	21.5"	1.5"	3.75"
20 Watt	25.5"	1.5"	3.75"

- 215040** - High Vision 15 Watt (18" long bulb) approx. shipping Wt. - 5 lbs.
- 215050** - High Vision 20 Watt (24" long bulb) approx. shipping Wt. - 7 lbs.

The unique combination of the reusable slip-on polycarbonate filter sleeve and a fluorescent bulb produce more visible light in the safe range than conventional safelights. High Vision Safelights are safe for use with all blue or green sensitive X-Ray film. Safelights must be mounted a minimum distance of 4 feet from film.

You save filter replacement costs when changing the fluorescent bulb because, unlike some safelights, the High Vision Safelight filter is reusable and does not need to be replaced with the bulb.

The safelight has a pull string on-off switch and comes with a six foot 3-conductor grounded cord set. Safelights operate on 118 volts 60 HZ AC .5 AMPS.

Finish: Baked on White Enamel.

SUPERLIGHT



WIDTH	HGT	DEPTH
10.25"	11"	3.25"

This ultrathin, tapered 8"x10" safelight is scientifically designed to direct light where it is most needed. It is constructed of extra heavy gauge steel and electrically welded in the corners. Only safelights made this more costly way can assure permanent light tightness. Tapered design adds both beauty and utility to this superior safelight. Comes with a six foot 3-conductor grounded cord set.

Finish: light gray baked enamel.

approx. shipping Wt. - 7 lbs.

- 302** - Superlight, Baked Enamel Finish, S&S 6B Filter
- 302K** - Superlight, Baked Enamel Finish, GBX-2 Filter

COMBINATION



WIDTH	HGT	DEPTH
10.25"	14.25"	3.75"

Only 3.75" deep, this two compartment all welded safelight features an 8"x10" safelight and a 4"x10" illuminator. The all steel welded housing permanently prevents any light leakage. Exceptionally shallow depth will allow convenient placement without obstruction. The safelight switch is mounted in the front and the illuminator switch is mounted on the side to avoid any chance of accidental lighting. Comes with a six foot 3-conductor grounded cord set.

Finish: light gray baked enamel.

approx. shipping Wt. - 11 lbs.


- 301** - Combination, S&S 6B Filter
- 300** - Combination, GBX-2 Filter

CHOICE OF FILTERS: **S&S 6B** for Blue sensitive film or **KODAK GBX-2** for Blue or Green sensitive film

ECONOMICAL

A sturdy economical steel safelight with an 8"x10" filter. It can be mounted on a wall or the tank backboard, or it can stand on a shelf. Comes with a six foot 3-conductor grounded cord set.

Finish: light gray baked enamel.
 approx. shipping Wt. - 9 lbs.




WIDTH	HGT	DEPTH
10.25"	10.25"	3.5"

- 300A** - Economical, S&S 6B Filter

CIRCULAR 3.5" SAFELIGHT

A compact, low cost 3.5" round safelight that screws into any standard



- 300B** - Circular, S&S 6B Filter

SAFELIGHTS OPERATE ON 118 VOLTS 60HZ AC .